

UNCLASSIFIED

AD NUMBER

**AD445307**

NEW LIMITATION CHANGE

TO

**Approved for public release, distribution  
unlimited**

FROM

**Distribution authorized to U.S. Gov't.  
agencies and their contractors;  
Administrative/Operational Use; 10 MAY  
1962. Other requests shall be referred to  
Air Force Systems Command, Attn: Space  
Systems Division, Los Angeles, CA  
90009-2960.**

AUTHORITY

**SSD, per DTIC Form 55**

THIS PAGE IS UNCLASSIFIED

THIS REPORT HAS BEEN DELIMITED  
AND CLEARED FOR PUBLIC RELEASE  
UNDER DOD DIRECTIVE 5200.20 AND  
NO RESTRICTIONS ARE IMPOSED UPON  
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;  
DISTRIBUTION UNLIMITED.

**UNCLASSIFIED**

**AD 445307**

**DEFENSE DOCUMENTATION CENTER**

**FOR**

**SCIENTIFIC AND TECHNICAL INFORMATION**

**CAMERON STATION, ALEXANDRIA, VIRGINIA**



**UNCLASSIFIED**

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

445307

AD No.

FILE COPY

⑤ THE BOEING COMPANY  
AERO-SPACE DIVISION


⑥ ROCKET PLUME RADIATION AND SUPPRESSION

⑭ CONTRACT AF 04(695)J22

⑨ First Monthly Letter Report no. 1,  
⑩ May 10, 1962

Prepared for

SPACE SYSTEMS DIVISION  
AIR FORCE SYSTEMS COMMAND  
AIR FORCE UNIT POST OFFICE  
LOS ANGELES 45, CALIFORNIA



625

646

## ROCKET PLUME RADIATION AND SUPPRESSION

### Program Objectives

The objectives of this program are to conduct analytical and laboratory studies of rocket plume radiation and techniques for plume radiation suppression. Experiments are to be conducted at reduced pressures to determine the spectral and spatial distribution of the radiation from selected liquid and solid propellant combinations, and to investigate means of reducing the infrared and ultraviolet radiation of rocket plumes by introducing fuel additives to these propellant combinations.

### Summary of Work Accomplished

Development of the test plan has been initiated. The proposed schedule is shown on the attached chart. The Boeing Jet Laboratory Group has prepared motor and facility design drawings in preparation for the initial experimental studies.

Infrared and optical instrumentation has been developed or improved as follows:

1. A Perkin-Elmer Model 98 monochromator has been modified for use through the ultraviolet, visible and near-infrared regions. It will scan from 0.2 to 1.2 microns in 0.2 to 0.5 seconds. Two photomultipliers, having S-1 and S-5 responses, are used with a beam splitter to allow operation over this spectral region. A three-inch diameter reflective collecting system has also been installed.

- + -

2. An ultraviolet-visible radiometer has been constructed. It uses the same photomultipliers as the ultraviolet-visible monochromator (Item 1) and will likewise be sensitive between 0.2 and 1.2 microns. Field limiting apertures are used in this instrument rather than collecting optics.
3. The 35 mm pulse camera, used in earlier work, will not be modified.
4. The Perkin-Elmer Model 108 rapid scan monochromator was examined and found optically satisfactory. This instrument provides spectral coverage from 1.2 to 5.5 microns.
5. Narrow band filters at 2.7 and 4.3 microns are being ordered for installation in the Barnes R4F2 dual-channel radiometer, according to specifications supplied by the project officer.
6. The audio-modulation radiometer has been completed and tested with a laboratory burner. Its lead sulfide detector drives two data channels. A d.c. channel records the plume radiance, and a 2 to 5000 cps channel records the audio-modulation component. Three-inch Cassegrain collecting optics are used with the system.
7. The total radiometer will be the same as used in previous tests. It is a Barnes R-8B1 radiometer with 3-inch optics attached and is filtered for 1.2 to 5.5 micron spectral coverage.

Activities Planned for May 1962

The infrared instrumentation will be completed.

1. The rapid scan monochromator rate will be reduced to 5 spectra per second. A chopped globar source will be constructed for transmission measurements in the infrared.
2. The scanning radiometer will be modified to allow operation out to 4.3 microns. A new window and scanning mirror installation is required for this modification.

Preliminary calibrations will be performed on the instruments as necessary. In particular, the ultraviolet-visible monochromator will be calibrated in wavelength and absolute intensity and used to cross calibrate several tungsten lamps. These lamps will in turn be used to calibrate the ultra-violet-visible radiometer.

Test preparations will proceed at Boeing Jet Laboratory, with goal of initial experimental runs in early June. Analytical studies of the effects of additives on solid propellant and non-hydrocarbon liquid propellant systems will be commenced. The trade-off studies of the total effect of tri-component radiation suppression on system performance will be started.

Submitted by:

  
J. M. Sutton  
Infrared and Optical Physics Group

Approved by:

E. L. Chupp  
Geo-Space Physics Unit

**PROPOSED PROGRAM SCHEDULE**  
**Rocket Plume Radiation and Suppression**  
**1962 - 1963**

